

**APPLICATION**

**FOR**

**UNITED STATES LETTERS PATENT**

**TITLE:**

**LIGHT MODULATOR HAVING PIXEL MEMORY  
DECOUPLED FROM PIXEL DISPLAY**

**INVENTOR:**

**THOMAS E. WILLIS**

Prepared By:  
Richard C. Calderwood  
Reg. No. 35, 468

Express Mail No. EL414998579US

1 LIGHT MODULATOR HAVING PIXEL MEMORY  
2 DECOUPLED FROM PIXEL DISPLAY

3 Related Applications

4 This application is a continuation-in-part application of U.S. Patent Application  
5 number 10/XXX,XXX, entitled Digitally Driving Pixels From Pulse Width Modulated  
6 Waveforms, filed on February 22, 2002.

7 Background

8 The present invention relates generally to displays, and more particularly, using  
9 pulse-width modulation to drive one or more display elements of an electro-optical  
10 display, for example, to digitally drive pixels from pulse width modulated waveforms in a  
11 liquid crystal display, such as a silicon light modulator with digital storage.

12 Pulse-width modulation (PWM) has been employed to drive liquid crystal  
13 displays (displays). A pulse-width modulation scheme may control displays, including  
14 emissive and non-emissive displays, which may generally comprise multiple display  
15 elements. In order to control such displays, the current, voltage or any other physical  
16 parameter that may be driving the display element may be manipulated. When  
17 appropriately driven, these display elements, such as pixels, normally develop light that  
18 can be perceived by viewers.

19 In an emissive display example, to drive a display (e.g., a display matrix having a  
20 set of pixels), electrical current is typically passed through selected pixels by applying a  
21 voltage to the corresponding rows and columns from drivers coupled to each row and  
22 column in some display architectures. An external controller circuit typically provides  
23 the necessary input power and data signal. The data signal is generally supplied to the  
24 column lines and synchronized to the scanning of the row lines. When a particular row is

1 selected, the column lines determine which pixels are lit. An output in the form of an  
 2 image is thus displayed on the display by successively scanning through all the rows in a  
 3 frame.

4 For instance, a silicon light modulator (SLM) uses an electric field to modulate  
 5 the orientation of a liquid crystal (LC) material. By the selective modulation of the liquid  
 6 crystal material, an electronic display may be produced. The orientation of the LC  
 7 material affects the intensity of light going through the LC material. Therefore, by  
 8 sandwiching the LC material between an electrode and a transparent top plate, the optical  
 9 properties of the LC material may be modulated. In operation, by changing the voltage  
 10 applied across the electrode and the transparent top plate, the LC material may produce  
 11 different levels of intensity on the optical output, altering an image produced on a screen.

12 Figure 7 illustrates a portion of a light engine or projector apparatus that utilizes  
 13 SLMs, as is known in the art. The projector includes a polarization beam splitter (PBS)  
 14 which passes light of a first polarization and reflects (at a 90 degree angle) light of a  
 15 second polarization. As illustrated, blue light of the first polarization and red light of the  
 16 second polarization enter the PBS, and the blue beam is passed through and the red beam  
 17 is reflected. Each beam is passed through a respective quarter-wave plate before striking  
 18 a respective SLM. Each SLM includes a pixel array for modulating the light, and a  
 19 reflective rear surface for reflecting the modulated beam back through the quarter-wave  
 20 plate to the PBS. The image-content-injected beams emerge from the PBS, and may then  
 21 be directed to e.g. a display device (not shown).

22 Typically, a silicon light modulator (SLM) is a display device where a liquid  
 23 crystal material (LC) is driven by circuitry located at each pixel. For example, when the  
 24 LC material is driven, an analog pixel might represent the color value of the pixel with a  
 25 voltage that is stored on a capacitor under the pixel. This voltage can then directly drive  
 26 the LC material to produce different levels of intensity on the optical output. Digital

pixel architectures store the value under the pixel in a digital fashion. In this case, it is not possible to directly drive the LC material with the digital information, i.e., there needs to be some conversion to an analog form that the LC material can use.

Pulse-width modulation (PWM) may be utilized for driving an SLM device. However, several conventional PWM schemes add up non-overlapping waveforms to build a PWM waveform. Unfortunately, these conventional ways of driving displays using a typical PWM scheme may not be adequate, as multiple edges may get generated in the PWM waveform. Using this approach, for example, the LC material may not be driven by a signal that is a function of the desired color value. Therefore, such a multi-edged PWM waveform that draws upon multiple non-overlapping pulses to build the PWM waveform for driving a display device or display system architecture may not precisely control the LC material being driven. Furthermore, this type of driving control that simply uses a fixed waveform may not be easily tuned to a particular LC material.

Thus, better ways are desired to drive display elements in displays, especially in digital pixel architectures.

#### Brief Description of the Drawings

Figure 1 is a schematic depiction of a display system according to an embodiment of the present invention;

Figure 2 is a block diagram of a linear silicon light modulator with digital storage employing linear pulse-width modulation (PWM), in accordance with one embodiment of the present invention;

Figure 3 is a block diagram of a nonlinear silicon light modulator with digital storage employing nonlinear pulse-width modulation, according to an alternate embodiment of the present invention;

1 Figure 4A is a hypothetical graph of applied voltage versus time for a silicon light  
2 modulator (SLM) in accordance with one embodiment of the present invention;

3 Figure 4B is a hypothetical graph of adjusted applied voltage versus time for a  
4 SLM in accordance with another embodiment of the present invention; and

5 Figure 5 is a flow chart of a PWM signal generator to digitally drive pixels from  
6 pulse width modulated waveforms in accordance with one embodiment of the present  
7 invention; and

8 Figure 6 is a flow chart of a control logic and a pixel logic consistent with one  
9 embodiment of the present invention.

10 Figure 7 illustrates a simplified projection system according to the prior art,  
11 employing two SLMs.

12 Figure 8 illustrates one embodiment of the light modulator.

13 Figure 9 illustrates another embodiment of the light modulator.

14 Figure 10 illustrates yet another embodiment of the light modulator.

15 Figure 11 illustrates one embodiment of a physical layout of the light modulator.

16 Figure 12 illustrates one embodiment of a method of operation of the invention.

### 17 Detailed Description

18 While it will have been clear to the skilled reader of the parent application that the  
19 presence of the term “silicon” in the phrase “silicon light modulator” is merely a  
20 convenient and customary description in the art, and that neither the various  
21 embodiments nor the claims of the parent application are limited to “silicon”, the inventor  
22 chooses to expressly make the point here. SLMs may be built using a variety of  
23 fabrication techniques, semiconductor materials, and so forth.

24 A display system 10 (e.g., a liquid crystal display (display), such as a silicon light  
25 modulator (SLM)) shown in Figure 1 includes a liquid crystal layer 18 according to an

1 embodiment of the present invention. In one embodiment, the liquid crystal layer 18 may  
2 be sandwiched between a transparent top plate 16 and a plurality of pixel electrodes 20(1,  
3 1) through 20(N, M), forming a pixel array comprising a plurality of display elements  
4 (e.g., pixels). In some embodiments, the top plate 16 may be made of a transparent  
5 conducting layer, such as indium tin oxide (ITO). Applying voltages across the liquid  
6 crystal layer 18 through the top plate 16 and the plurality of pixel electrodes 20(1, 1)  
7 through 20(N, M) enables driving of the liquid crystal layer 18 to produce different levels  
8 of intensity on the optical outputs at the plurality of display elements, i.e., pixels,  
9 allowing the display on the display system 10 to be altered. A glass layer 14 may be  
10 applied over the top plate 16. In one embodiment, the top plate 16 may be fabricated  
11 directly onto the glass layer 14.

12 A global drive circuit 24 may include a processor 26 to drive the display system  
13 10 and a memory 28 storing digital information including global digital information  
14 indicative of a common reference and local digital information indicative of an optical  
15 output from at least one display element, i.e., pixel. Based on a comparison of the global  
16 and local digital information, the display system 10 may determine a transition separating  
17 a first pulse interval and a second pulse interval in a modulated signal generated for at  
18 least one display element, i.e., pixel. Accordingly, from the modulated signal, the display  
19 element may be appropriately driven, providing the optical output based on the digital  
20 information.

21 In some embodiments, the global drive circuit 24 applies bias potentials 12 to the  
22 top plate 16. Additionally, the global drive circuit 24 provides a start signal 22 and a  
23 digital information signal 32 to a plurality of local drive circuits (1, 1) 30a through (N, 1)  
24 30b, each local drive circuit may be associated with a different display element being  
25 formed by the corresponding pixel electrode of the plurality of pixel electrodes 20(1, 1)  
26 through 20(N, 1), respectively.

1 In one embodiment, a liquid crystal over silicon (LCOS) technology may be used  
2 to form the display elements of the pixel array. Liquid crystal devices formed using the  
3 LCOS technology may form large screen projection displays or smaller displays (using  
4 direct viewing rather than projection technology). Typically, the liquid crystal (LC)  
5 material is suspended over a thin passivation layer. A glass plate with an indium tin  
6 oxide (ITO) layer covers the liquid crystal, creating the liquid crystal unit sometimes  
7 called a cell. A silicon substrate may define a large number of pixels. Each pixel may  
8 include semiconductor transistor circuitry in one embodiment.

9 One technique in accordance with an embodiment of the present invention  
10 involves controllably driving the display system 10 using pulse-width modulation  
11 (PWM). More particularly, for driving the plurality of pixel electrodes 20(1,1) through  
12 20(N, M), each display element may be coupled to a different local drive circuit of the  
13 plurality of local drive circuits (1, 1) 30a through (N, 1) 30b, as an example. To hold  
14 and/or store any digital information intended for a particular display element, a plurality  
15 of digital storage (1, 1) 35a through (N, 1) 35b may be provided, each digital storage may  
16 be associated with a different local drive circuit of the plurality of local drive circuits (1,  
17 1) 30a through (N, 1) 30b, for example. Likewise, for generating a pulse width  
18 modulated waveform based on the respective digital information, a plurality of PWM  
19 devices (1, 1) 37a through (N, 1) 37b may be provided in order to drive a corresponding  
20 display element. In one case, each PWM device of the plurality of PWM devices (1, 1)  
21 37a through (N, 1) 37b may be associated with a different local drive circuit of the  
22 plurality of local drive circuits (1, 1) 30a through (N, 1) 30b.

23 Consistent with one embodiment of the present invention, the global drive circuit  
24 24 may receive video data input and may scan the pixel array in a row-by-row manner to  
25 drive each pixel electrode of the plurality of pixel electrodes 20(1,1) through 20(N, M).  
26 Of course, the display system 10 may comprise any desired arrangement of one or more

display elements. Examples of the display elements include silicon light modulator devices, emissive display elements, non-emissive display elements and current and/or voltage driven display elements.

Generally, a silicon light modulator (SLM) is a display device where a liquid crystal material (LC) is driven by circuitry located under each pixel. Of course, there are many reasonable pixel architectures for these devices, each of which have implications on how the LC material is driven. For example, an analog pixel might represent the color value of the pixel with a voltage that is stored on a capacitor under the pixel. This voltage can then directly drive the LC material to produce different levels of intensity on the optical output. Digital pixel architectures store the value under the pixel in a digital fashion. In this case, it is not possible to directly drive the LC material with the digital information, i.e., there needs to be some conversion to an analog form that the LC material can use. Therefore, pulse-width modulation (PWM) is utilized for generating color in an SLM device in one embodiment of the present invention. This enables pixel architectures that use pulse-width modulation to produce color in SLM devices. In this approach, the LC material is driven by a signal waveform whose "ON" time is a function of the desired color value.

More specifically, one embodiment of the display system 10 may be based on a digital system architecture that uses pulse-width modulation to produce color in silicon light modulator devices arranged in a matrix array comprising a plurality of digital pixels, each digital pixel including one or more sub-pixels. In one case, the matrix array may include a plurality of columns and a plurality of rows. The columns and rows may be driven by a separate global drive circuit, which may enable localized generation of a pulse width modulated voltage or current waveforms at a digital pixel level to drive the plurality of digital pixels. Alternatively, the plurality of digital pixels may be configured in any other useful or desirable arrangement.



1 In essence, to digitally drive the digital pixels according to the present invention,  
2 one operation may involve storing respective digital information received over the digital  
3 information signal 32 at each digital storage 37 associated with a different local drive  
4 circuit 30, for driving an associated pixel electrode 20 of the corresponding display  
5 element, for example. To indicate the lengths of the first and second pulse intervals  
6 forming the modulated signal, a particular timing providing a desired transition may be  
7 derived based on the digital information. In turn, the lengths of the first and second pulse  
8 intervals of the modulated signals may control the optical output of each display element  
9 within a refresh period.

10 For some embodiments, providing the local digital information may include  
11 dynamically receiving video data associated with each display element. However,  
12 receiving the video data, in one embodiment, includes programmably receiving at least  
13 one pixel value for each display element. The digital information may be programmably  
14 stored in at least one register associated with each display element. Then, for each  
15 display element, a duration of illumination, i.e., an "ON" time within the refresh period  
16 may be caused based on the length of the first pulse interval of the modulated signal.

17 When the display element receives the global and local digital information, the  
18 global digital information may be compared to the local digital information to determine  
19 a desired timing for a particular single transition in the modulated signal. As a result, this  
20 comparison may cause the particular single transition to occur in the modulated signal  
21 applied to the display element. Moreover, by varying the duration of application of the  
22 modulated signal to the display element, however, an optical output from the display  
23 element may be selectively adjusted based on this comparison. This selective adjustment  
24 feature may be utilized to compensate for a display nonlinearity of one or more display  
25 elements in one embodiment. To further nonlinearly modulate the optical output from  
26 the display element, the particular single transition may also be selectively delayed.

Following the general architecture of the display system 10 of Figure 1, a linear silicon light modulator (SLM) 50 shown in Figure 2 includes a controller A 55 to controllably operate the linear SLM 50. For the purposes of storing digital information, the linear SLM 50 may further include a pixel source A 60. The pixel source A 60 stores pixel data A 65 comprising digital information that may include global digital information and local digital information in accordance with one embodiment of the present invention.

Although the scope of the present invention is not limited in this respect, pixel source A 60 may be a computer system, graphics processor, digital versatile disk (DVD) player, and/or a high definition television (HDTV) tuner. In addition, pixel source A 60 may not provide pixel data A 65 for all of the pixels in the display system 10. For example, the pixel source A 60 may simply provide the pixels that have changed since the last update since in some embodiments having appropriate storage for all the pixel values, it will ideally know the last value provided by the pixel source A 60.

The linear SLM 50 may further comprise a plurality of signal generators 70(1) through 70(N), each signal generator associated with at least one display element. Each signal generator 70 may be operably coupled to the controller A 55 for receiving respective digital information. When appropriately initialized, each signal generator 70 may determine a transition in a linearly pulse width modulated waveform based on the digital information to drive a different display element.

As shown in Figure 2, in one embodiment, the controller A 55 may incorporate a control logic A 75 and a counter 80 (e.g., n-bit wide). The control logic A 75 may controllably operate each display element based on respective digital information. To this end, the counter 80 may provide global digital information indicative of a dynamically changing common reference, i.e., a count, to each display element.

1 In the illustrated embodiment, each signal generator 70 of the plurality of signal  
 2 generators 70(1) through 70(N), may comprise a respective register 85 of a plurality of  
 3 registers 85(1) through 85(N), a respective comparator 92 of a plurality of comparators  
 4 92(1) through 92(N), a respective PWM driver circuitry 94 of a plurality of PWM driver  
 5 circuitry 94(1) through 94(N) to drive a corresponding pixel electrode 96 of a plurality of  
 6 pixel electrodes 96(1) through 96(N). Each register 85 of the plurality of registers 85(1)  
 7 through 85(N) may retain for further processing the associated digital information  
 8 including a corresponding pixel value 90 of a plurality of pixel values 90(1) through  
 9 90(N) and/or the count to generate a corresponding linearly pulse width modulated  
 10 waveform.

11 Again, following the general architecture of the display system 10 of Figure 1, a  
 12 nonlinear silicon light modulator (SLM) 100 shown in Figure 3 includes a controller B  
 13 105 to controllably operate the nonlinear SLM 100. The nonlinear SLM 100 may further  
 14 include a pixel source B 110 for storing digital information. In accordance with one  
 15 embodiment of the present invention, the pixel source B 110 stores pixel data B 115  
 16 comprising digital information that may include global digital information and local  
 17 digital information associated with one or more display elements. The nonlinear SLM  
 18 100 may further comprise a plurality of signal generators 120(1) through 120(M) where  
 19 each signal generator 120 may be operably coupled to the controller B 105 for receiving  
 20 respective digital information for operating any associated display element. In operation,  
 21 a single transition in a nonlinearly pulse width modulated waveform to drive a different  
 22 display element, may be determined by each signal generator 120 based on the digital  
 23 information provided and when appropriately initialized.

24 Referring to Figure 3, in one embodiment, the controller B 105 may include a  
 25 control logic B 125, a counter 130 (e.g., m-bit wide), and a look-up-table (LUT) 132.  
 26 Each display element may be nonlinearly operated by the control logic B 125 based on

1    respective digital information retrieved from the LUT 132. Here, again global digital  
2    information indicative of a dynamically changing common reference, i.e., a count, may  
3    be provided to each display element by the counter 130 via the LUT 132.

4            Each signal generator 120 of the plurality of signal generators 120(1) through  
5    120(M), in the depicted embodiment, may comprise a respective register 135 of a  
6    plurality of registers 135(1) through 135(M), a respective comparator 142 of a plurality of  
7    comparators 142(1) through 142(M), a respective PWM driver circuitry 144 of a plurality  
8    of PWM driver circuitry 144(1) through 144(M) to drive a corresponding pixel electrode  
9    146 of a plurality of pixel electrodes 146(1) through 146(M). Each register 135 of the  
10   plurality of registers 135(1) through 135(M) may store the associated digital information  
11   including a corresponding pixel value 140 of a plurality of pixel values 140(1) through  
12   140(M) and the count to generate a corresponding nonlinearly pulse width modulated  
13   waveform. As described earlier in the context of the linear SLM 50 of Figure 2, in a  
14   similar fashion, the corresponding nonlinearly pulse width modulated waveform may be  
15   formed for a corresponding pixel electrode 146 of a plurality of pixel electrodes 146(1)  
16   through 146(M).

17            Figure 8 shows another embodiment of the invention. A display system 310  
18   includes a pixel source 312 which sends pixel data values to a pixel storage 314 over a  
19   suitable communication link 313. In the simplified example shown, the pixel storage is  
20   represented as being only a register or other suitable storage for storing a single pixel's  
21   data value; however, the skilled reader will understand that this simplification is only for  
22   ease in explanation. The pixel storage provides its stored value as a first (A) input to a  
23   comparator 316. In the illustrated embodiment, the comparator performs a "greater than  
24   or equal to" comparison, as denoted by " $A \geq B$ ?" Other comparisons may be used in  
25   other embodiments, such as " $A > B$ ?" or " $A \leq B$ ?" with appropriate modification to the  
26   PWM scheme and counter. (For example, the counter could count downward and the

1 pixel could be turned ON when the appropriate count value is reached, rather than being  
2 turned off as in the illustrated embodiment.) Furthermore, the reader will appreciate that  
3 digital functions other than comparison could be employed, and that a comparison is only  
4 one example of a suitable digital function.

5 The other (B) input to the comparator comes from a global counter 318. The  
6 counter is an n-bit counter, wherein "n" is the number of bits of color depth in the  
7 particular pixel. The skilled reader will appreciate that, in various embodiments of the  
8 system, there may be more than one such global counter 318. For example, a particular  
9 application may call for a red-green-blue (RGB) color scheme using 16 bits to represent  
10 the three sub-pixels, and in which red and blue each have five bits and green has six bits  
11 of the sixteen. In such a case, the "green pixels" (which may alternatively be called  
12 sub-pixels) may be driven by a global six-bit counter, while the red and blue sub-pixels  
13 may be driven by a global five-bit counter. In other embodiments, a single, configurable  
14 or programmable counter may be used in an interleaved or time-sliced mode in which, for  
15 example, it counts to a first value for the red pixels, a second value for the green pixels,  
16 and a third value for the blue pixels. The skilled reader will appreciate other such  
17 permutations of this invention, in view of this disclosure. For example, the invention is  
18 not limited to use in the RGB color space. As another example, the invention may find  
19 utility outside the realm of SLMs, such as in driving flat panel plasma or LCD displays or  
20 the like.

21 The counter and the comparator are controlled by control logic 320 over links 319  
22 and 321, respectively. The output of the comparator is provided to the pixel electrode 326  
23 which controls the display of the liquid crystal pixel 328. In embodiments in which the  
24 output of the comparator is not suitable for directly powering the electrode, the output  
25 may be buffered or otherwise enhanced, such as by a D flip-flop 322 and other suitable  
26 means (not shown).

1           Figure 9 illustrates an embodiment of the invention, similar to that of Figure 8  
2 but, rather than illustrating only a single pixel's associated circuitry, multiple pixels'  
3 circuitry 330 is shown. The pixel source feeds a memory array 332, whose contents are  
4 provided to multiple comparators (such as one per column, typically), which in turn drive  
5 a pixel array 334. The memory array is indicated as an "nx by y memory array" to  
6 suggest that it is x rows by y columns, and n bits per pixel (or, more accurately,  
7 sub-pixel).

8           The memory array 332 is physically decoupled and distinct from the pixel array.  
9 This enables the memory array and pixel array to scale independently. That is,  
10 improvements or changes in the circuitry, configuration, layout, size, etc. of one of them  
11 can be made independently of any such changes (or lack thereof) in the other. It may  
12 often be the case that the pixel array cells (each of which may now typically include in its  
13 driver circuitry a comparator, a flip-flop, and an electrode) can be manufactured at a  
14 much smaller size than if each were also required to include a storage device for storing  
15 the pixel value. It may also be the case that the separated pixel array and memory array  
16 can be fabricated on more convenient areas of a die, on separate die, or even using  
17 different fabrication or semiconductor technologies.

18           Figure 10 illustrates another embodiment of a system 340 utilizing this invention.  
19 This embodiment is of the lookup table variety discussed above, and includes the distinct  
20 memory array and pixel array, as well as the lookup table 342 and m-bit counter 344.

21           The reader will appreciate that, while Figures 9 and 10 illustrate embodiments in  
22 which an nx-by-y memory array drives an x-by-y pixel array, other configurations of the  
23 memory array are within the scope of this invention. For example, the memory array  
24 could be built as an nx/2-by-2y array, or any other configuration suitable to the  
25 application at hand. The reader will also appreciate that various other embodiments of  
26 utilizing the comparators are within the scope of this invention. For example, rather than

1 having one comparator per column, adjacent columns could share a time-multiplexed  
2 comparator. Or, all columns could share a single time-multiplexed comparator. At the  
3 other extreme, each pixel could have its own comparator.

4 Figure 11 illustrates one exemplary layout of a spatial light modulator 350  
5 constructed according to the principles of this invention. The light modulator may include  
6 a source input at which it receives pixel data values from an external pixel source.  
7 Alternatively, the pixel source may be integral with the light modulator. The pixel data  
8 are provided from the source input to a pixel memory array, which may be arranged in  
9 rows and columns. In the example shown, there are eight rows of pixel data (R0 to R7),  
10 and eight columns of pixel data (C0 to C7), and a redundant column (Cr) which may be  
11 utilized, using conventional means, for providing redundancy and repair facilities such  
12 that the memory array as a whole continues to function even with the loss of one or more  
13 of its memory cells, as is well understood in the art.

14 Control logic provides control signals to the pixel memory array, to a pixel  
15 display array, and to the counter. Alternatively, a lookup table (LUT) may be employed,  
16 as explained above.

17 The pixel memory array and the pixel display array are physically distinct. That  
18 is, the cells of the pixel memory array (or at least some of them, in some embodiments)  
19 are located outside the boundaries of the pixel display array. The circuitry required  
20 beneath each display pixel is thus reduced, by moving at least its associated pixel data  
21 value storage cell to the outside location. The size of each display pixel can be reduced,  
22 and thus the resolution of the display is improved. The PWM update is decoupled from  
23 the pixel value update. This may, in some cases, enable a higher quality display. The  
24 memory array can be whatever size it needs to be, generally without impacting the  
25 display pixel size. Redundant memory cells, and other desirable features, can be added to  
26 the memory array generally without impacting the size of the pixel display or its

1 individual cells. In some embodiments, it may prove desirable to provide some level of  
2 storage within some or all of the pixel display array cells, while also providing additional  
3 pixel data value storage outside the display area.

4 Alternatively, Figure 11 may be understood to represent a liquid crystal display, a  
5 plasma display, organic light emitting diode (OLED) display, or other such display in  
6 which each pixel is independently driven (as opposed to a cathode ray tube, in which all  
7 pixels are commonly driven by a modulated beam).

8 The skilled reader should appreciate that it is not necessary that all pixels in the  
9 display be of the same shape or size, nor that the display array be rectangular or regular.  
10 In some applications, it may be desirable that only a subset of the pixels in the display be  
11 built according to this invention. For example, a display might have a low-resolution area  
12 in which the pixels are large enough that it is acceptable, or perhaps even desirable, that  
13 the pixel value storage be located under the respective pixel display cells, and a  
14 high-resolution area in which this invention is employed and the pixel storage is located  
15 elsewhere. In such cases, the pixel storage could be located remotely from the entire  
16 display, or it might be located under the low-resolution area's cells. A wide variety of  
17 configurations will be appreciated, in light of this disclosure.

18 A hypothetical graph of an applied voltage versus time, i.e., a drive signal (e.g., a  
19 PWM waveform) is shown in Figure 4A for a silicon light modulator in accordance with  
20 one embodiment of the present invention. Within a first refresh time period,  $T_r$ , 150a, the  
21 drive signal including a first transition 155a and during the next cycle, i.e., within a  
22 second refresh time period,  $T_r$ , 150b, the drive signal including a second transition 155b  
23 may be applied to the pixel electrode 96(1) of Figure 2, for example. Each transition of  
24 the first and second transitions 155a, 155b, separates the drive signal in a first and second  
25 pulse intervals. The first pulse interval of the second refresh time period 150b is  
26 indicated as the "ON" time,  $T_{on}$ , as an example.



In some embodiments, the “ON” time,  $T_{on}$ , of the drive signal of Figure 4A is a function,  $f_{pwm}$ , of the current pixel value,  $p$ , where  $p \in [0, 2^n - 1]$ ,  $n$  is the number of bits in a color component (typically 8 for some computer systems),  $T_{on} \in [0, T_r]$ , and  $T_r$  is a constant refresh time. For example, if  $f_{pwm}$  is linear, then  $T_{on}$  may be given by the following equation:

$$T_{on} = f_{pwm}(p) = \frac{p}{2^n - 1} T_r \quad (1)$$

The first and second refresh time periods, i.e.,  $T_r$ , 150a and 150b, may be determined depending upon the response time, i.e.,  $T_{resp}$ , of the liquid crystal (LC) material along with an update rate, i.e.,  $T_{update}$ , (e.g., the frame rate) of the content that the display system 10 (Figure 1) may display when appropriately driven. Ideally, the refresh time periods, i.e.,  $T_r$ , 150a and 150b may be devised to be shorter than that of the update rate,  $T_{update}$ , of the content, and the minimum “ON” time, minimum ( $T_{on}$ ), may be devised to be larger than the response time,  $T_{resp}$ , of the LC material. However,  $T_{on}$ , may be time varying as a pixel value “ $p$ ” may change over time.

It is often desirable to use a non-linear function for  $f_{pwm}$  to match this function with other non-linear aspects of the display system 10. The function  $f_{pwm}$  may be realized through a variety of conventional hardware. As the function  $f_{pwm}$  is a function of the pixel value “ $p$ ,” some portion of this hardware may be locally disposed at each pixel in the display system 10, e.g., the linear SLM 50 of Figure 2 or the nonlinear SLM 100 of Figure 3. In any event, by advantageously moving as much of the functionality as possible into components that can be globally shared, i.e., within the global drive circuit 24 of Figure 1, this hardware portion that is disposed locally at each pixel may be significantly reduced. As an example, Figure 3 illustrates an SLM that uses this approach. In this example, the display system 10 employs the LUT 132 to generate the PWM function  $f_{pwm}$  that is non-linear in nature.

1 Another useful feature according to one embodiment of the present invention  
 2 enables the display system 10 to adjust the portion of the first and second refresh time  
 3 periods, i.e.,  $T_r$ , 150a and 150b, that is devoted to the PWM waveform. By adding  
 4 additional delay, the LCD system 10 can produce an adjusted PWM waveform shown in  
 5 Figure 4B, which shows another hypothetical graph of the applied voltage versus time  
 6 that is selectively adjusted to provide an adjusted drive signal as shown for a silicon light  
 7 modulator according to one embodiment of the present invention. During a refresh time  
 8 period,  $T_r$ , 150c the applied voltage may be adjusted to form the adjusted drive signal to  
 9 include a delayed transition 155c, providing an adjusted "ON" time,  $T_{on}$ , 160a.

10 As shown in Figures 2 and 3, in one embodiment, either one of the controllers A  
 11 55 or B 105 may operate as follows. In step 1, either one of the control logics A 75 or B  
 12 125 may present a "start" signal (e.g., the start signal 22 of Figure 1) to each PWM driver  
 13 circuitry (N) 94 or (M) 144, which may generate a corresponding PWM waveform for the  
 14 attached pixel at each pixel electrode of the pixel electrodes (N) 96 or (M) 146. In step 2,  
 15 each PWM driver circuitry (N) 94, or (M) 144 in each pixel turns its output "ON" in  
 16 response to the "start" signal.

17 The n-bit counter 80 (where "n" may be the number of bits in a color component)  
 18 may begin counting up from zero at a frequency given by  $2^n/T_r$  in step 3. In step 4, each  
 19 pixel monitors the counter value using comparator circuits (N) 92 that compares two n-bit  
 20 values, i.e., the counter and pixel values "c," "p" for equality. An n-bit register (N) 85  
 21 may hold the current pixel value for each pixel. When a pixel finds that the counter value  
 22 "c" is equal to its pixel value "p," the PWM driver circuitry (N) 94 turns its output  
 23 "OFF." This process repeats in an iterative manner by repetitively going back to the step  
 24 1 based on a particular implementation.

25 Forced delays may be introduced in some embodiments to generate an adjusted  
 26 PWM waveform, for example, having a time period indicated as  $T_{pwm}$  165. In particular,

1 a first force "ON" time,  $T_{fl}$ , 170a, and a second force "ON" time,  $T_{fo}$ , 170b, may be  
2 introduced in one embodiment. Adding additional delay between the steps 2 and 3  
3 creates the first force "ON" time,  $T_{fl}$ . Adding additional delay between the steps 3 and 4  
4 creates the second force "OFF" time,  $T_{fo}$ . Although adding these times can bound the  
5 minimum and maximum portion of the first and second refresh time periods, i.e.,  $T_r$  150a  
6 and 150b, that is spent within the PWM waveform during the "ON" state, however, a new  
7 PWM waveform with a single transition may still be generated accordingly.

8 At each pixel, the output waveform of the PWM driver circuitry (N) 94 (which  
9 drives the LC material) is "ON" for "p" counter increments (p is the pixel value).  
10 Because there are  $2^n$  clock ticks each refresh time,  $T_r$ , this generates a linear PWM  
11 waveform given by Equation (1). The logic necessary to load video data (e.g. pixel  
12 values) into the pixel array is not shown. However, if the video data, i.e., a pixel value  
13 load occurs asynchronously to the PWM behavior, either one of the control logics A 75  
14 may direct the PWM driver circuitry (N) 94 to turn "OFF" its output when writing a  
15 value less than the current counter value into any pixel. With appropriate design, the  
16 logic to perform this additional comparison can be located outside of the pixel array since  
17 this operation does not depend on a pixel value.

18 Since transfer curves for most LC material are non-linear, it is desirable to be able  
19 to generate non-linear PWM functions. Figure 3 illustrates a modified version of the  
20 system shown in Figure 2 that allows for non-linear PWM functions,  $f_{pwm}$ . In this figure,  
21 the counter value "c" that is provided to the pixels comes from the look-up-table (LUT)  
22 132. The values in the LUT 132 may be monotonically increasing and in the interval  $[0, 2^n-1]$ ,  
23 for example. The LUT 132 is indexed by the output of the m-bit counter 130 that  
24 operates at a higher frequency,  $2^m/T_r$ , than the n-bit counter 80 from Figure 2 (i.e.,  $m > n$ ).

25 In this way, the LUT 132 in conjunction with the m-bit counter 130 may allow the  
26 nonlinear SLM 100 to quantize the refresh interval into  $2^m$  intervals (where  $m > n$ ) so that

1 it can provide a fine control over the duration of the “ON” times for a PWM waveform  
 2 according to one embodiment. Accordingly, the embodiment in Figure 3 may add non-  
 3 linearity by chopping up the refresh time into smaller chunks ( $2^m$  chunks, specifically)  
 4 and then use the LUT 132 to map the smaller chunks onto pixel values. For example, at  
 5 count “i,” all pixels with value “p” (i.e.,  $LUT[i] = p$ ) may be turned “OFF.” By  
 6 appropriately programming the LUT 132, non-linear PWM functions may be suitably  
 7 furnished. Likewise, using the LUT 132, in some embodiments, forced delays may also  
 8 be introduced by programming the transitions for pixel values to occur after the m-bit  
 9 counter 130 reaches a value that corresponds to the force “ON” time and by making sure  
 10 that all pixel values transition before the force “OFF” time.

11 By selecting the values in the LUT 132, the time that a given n-bit value is  
 12 presented to the pixels may be suitably varied (note that in the linear case, all n-bit values  
 13 are presented to the pixel for the same duration). Instead of varying the m-bit counter  
 14 130 signal over time as is done in Figure 3, it is also possible to allow for non-linear  
 15 PWM functions by changing the rate at which the counter 130 circuit is clocked by  
 16 dynamically changing this clocking signal with a voltage-controlled oscillator. By  
 17 allowing the ability to program the values in the LUT 132 dynamically, the PWM  
 18 function,  $f_{pwm}$  may be tuned to a specific transfer curve associated with the LC material  
 19 that, e.g., the display system 10 of Figure 1 may use.

20 A PWM signal generator 175 (i.e., either a combination of all the plurality of the  
 21 signal generators 70(1) through 70(N) of Figure 2 or a combination of all the plurality of  
 22 the signal generators 120(1) through 120(N) of Figure 3) is shown in Figure 5 to digitally  
 23 drive pixels from pulse width modulated waveforms in accordance with one embodiment  
 24 of the present invention. While the scope of the present invention is not so limited in this  
 25 respect, a single pass through the PWM signal generator 175 for one refresh period or  
 26 interval is illustrated in Figure 5, as an example.

1 Each register 85 (Figure 2) of the plurality of registers 85(1) through 85(N) may  
 2 dynamically receive video data associated with a different display element to cause the  
 3 “ON” time within the refresh period based on the corresponding linearly pulse width  
 4 modulated waveform at block 180. Corresponding digital information including video  
 5 data having a corresponding pixel value may be programmably received at each display  
 6 element. More specifically, each register 85 of the plurality of registers 85(1) through  
 7 85(N) may store the corresponding pixel value 90 of the plurality of pixel values 90(1)  
 8 through 90(N) at block 182.

9 At each pixel electrode 96 (Figure 2) of the plurality of the pixel electrodes 96(1)  
 10 through 96(N), the start signal 22 (Figure 1) may be received in block 184. Each PWM  
 11 driver circuitry 94 (Figure 2) of the plurality of PWM driver circuitry 94(1) through  
 12 94(N) may form a respective pulse width modulated waveform based on associated  
 13 digital information at the pixel at block 186. According to one embodiment, each signal  
 14 generator 70 (Figure 2) of the plurality of signal generators 70(1) through 70(N) may  
 15 determine the timing for a single transition to form the corresponding pulse width  
 16 modulated waveform based on the current digital information at block 188.

17 When provided, the single transitions of the corresponding pulse width modulated  
 18 waveforms may control the optical outputs from the associated display elements within a  
 19 refresh period. Additionally, each signal generator 70 of the plurality of signal generators  
 20 70(1) through 70(N) may drive an associated display element from the corresponding  
 21 pulse width modulated waveform, providing a dynamically changing optical output based  
 22 on the current digital information made available.

23 A check at the diamond 190 may provide a desired transition in each pulse width  
 24 modulated waveform driving the associated display element, as each comparator 92  
 25 (Figure 2) of the plurality of comparators 92(1) through 92(N) may compare the global  
 26 digital information, i.e., the count with the local digital information. If determined to be

4 To digitally drive pixels from pulse width modulated waveforms, a control logic  
5 200 (e.g., for the global drive circuit 24 of Figure 1) and a pixel logic 205 (e.g., for each  
6 local drive circuit of the plurality of local drive circuits (1, 1) 30a through (N, 1) 30b of  
7 Figure 1) consistent with one embodiment of the present invention are shown in Figure 6.  
8 For the ease of the presentation, a hypothetical dotted line 210 functionally distinguishes  
9 the control logic 200 from the pixel logic 205. According to one embodiment, to provide  
10 digital information entails sending a pixel value to each display element at block 215  
11 using the control logic 200. A corresponding pixel value may be received at each display  
12 element for storage in a register located at each display element at block 217. At block  
13 219, the start signal 22 (Figure 1) may also be sent from the control logic 200 to each  
14 display element.

Specifically, to drive the display element, e.g., the pixel, the start signal 22 (Figure 1) may be properly received at the pixel logic 205 at block 221. A count may be started by the control logic 200 at block 223 for iteratively providing multiple count values to the pixel logic 205. A check at diamond 225 may compare the current count value "COUNT" to a predefined value, for example, a maximum value "MAX." If the "COUNT" is determined to be same as that the "MAX," a first refresh interval is over and another pass may begin. Conversely, a looping sequence occurs by first incrementing the "COUNT" at block 227, and then returning for another comparison to the diamond 225. However, in accordance with one embodiment, each incremented "COUNT" may be iteratively reported back to the pixel logic 205 at block 229 until the "COUNT" reaches the "MAX." In this way, cooperatively the control logic 200 and pixel logic 205 go through a single pass during a single refresh period. This routine may

1 be repeated based on a particular application, desiring a display over multiple refresh  
2 periods.

3 By starting the count in block 223 for subsequent reporting thereof to each display  
4 element, and responsive to the start signal 22 (Figure 1) and the count at block 233, a  
5 modulated signal may be generated accordingly for each display element. In doing so,  
6 the pixel value may be compared to the count at block 235; the timing of a respective  
7 single transition may be determined to drive each display element.

8 In this way, based on a determination for timing of a prospective single transition  
9 for each display element, a single transition may be suitably caused in each modulated  
10 signal at block 237. When the global and local digital information, i.e., the pixel value  
11 and the count are substantially equal, one transition may be caused from an "ON" logic  
12 state to an "OFF" logic state in the modulated signal, as an example, stopping the display  
13 at block 239. On the other hand, another transition may be caused from an "OFF" logic  
14 state to an "ON" logic state in the modulated signal when the global and local digital  
15 information are different, iterating back to receive a new count at the block 233.

16 Thus, one embodiment of the present invention locally generates a PWM  
17 waveform to digitally drive a pixel. The PWM waveform includes a single "ON" pulse  
18 rather than the addition of non-overlapping "ON" pulses (i.e., there is a single "ON" to  
19 "OFF" transition in the PWM waveform each refresh period). Moreover, the PWM  
20 waveform may be a non-linear function of the pixel value. In addition, the PWM  
21 waveform may be programmed to match the transfer characteristics of the LC material.

22 Such a single "ON" pulse based technique may afford several advantages in one  
23 embodiment of the present invention. For instance, by providing a single "ON" pulse, a  
24 display device or display system architecture (e.g., digital pixel architectures for a digital  
25 SLM device) may better control the LC material being driven. In contrast, this type of  
26 control may be significantly lacking in some situations with approaches that add up

1 multiple non-overlapping pulses to build the PWM waveform. By allowing total  
2 programmability of the PWM waveform, in one embodiment, the display device or  
3 display system architecture may be relatively better tuned to a particular LC material than  
4 a system that simply uses a fixed waveform, as this scheme may allow the duty cycle of  
5 the fixed waveform to vary either as a linear or nonlinear function of pixel value with a  
6 single "ON" pulse.

7 Figure 12 illustrates one embodiment of a method 400 of operation of the  
8 invention. A pixel value is received (401) from the pixel value source. A counter value is  
9 received (402) from the global counter. A digital function is performed (403) on the  
10 counter value and the pixel value. As described above, the digital function may be a  
11 comparison, or other suitable operation. If (404) the digital operation gave a first result  
12 ("0"), the pixel is turned off (405). Otherwise, if the digital operation gave a second result  
13 ("1"), the pixel is turned on (406). The reader will appreciate that the digital operation  
14 need not be a binary operation.

15 The reader will further appreciate that, in many embodiments, it will be desirable  
16 to maintain some degree of synchronization between the counter update events, the pixel  
17 value events, and the display commit events. In one typical embodiment, the pixel values  
18 may arrive asynchronously with regard to the counter increment events, but the pixel  
19 commit events may be synchronized with the counter events such that the commit only  
20 happens when the counter has reached the end of a counter cycle, such as when it wraps  
21 (407) back around to an initial value such as zero. This synchronization will help avoid  
22 presentation of false pixel values to the display, or, in other words, latching  
23 incompletely-ramped values to the output.

24 At the appropriate synchronization time, if (408) the region update has not been  
25 completed, operation continues by receiving a next pixel value (401). Otherwise, the new  
26 pixel values are committed (409) to the display. Then, operation can continue with



